

ESP-103 Card Reader



Product Features

- Easy installation system with high speed operating
- Embedded LINUX system, easy to integrate into various system
- Standalone or network environment
- Built-in access controller, Support 99 time zones, 5 groups, 10 door-opening combinations
- 24 hours continuous operation available
- Saves data during power outage
- More security, multiplex alarm alert support

Features

LCD Display	4 lines Character white LCD 128*64
Card Capacity	30,000 cards
Log Capacity	50,000 transactions
Identification speed (1:N)	≤ 20ms
Communication	TCP/IP, RS232/485, USB Host, Wiegand In/out
Power Supply	110/220VAC ~ 12VDC
Operating Temperature	0°C ~ 45°C
Standard Function	Professional access control, built-in relay, 50 time zones, 5 groups and 10 combinations; Dismantlement alarm, break-in alarm, duress alarm; door sensor; Support wired door bell connection; 9-PIN ID, Auto status, Work code, SMS
Operating Humidity	20% ~ 80%
Access Mode	Card only, PIN only, Card + PIN
Attendance status	Check in, Check out
Size	125(L)*95(W)*45(H)mm



EFFICIENT SYSTEMS PTE LTD

BLK 52, UBI AVE 3, #03-42 FRONTIER, SINGAPORE 408867

TEL: +65 68582880 FAX: +65 67435906

www.efficient.com.sg