



ESP-6KX Card Reader

Product Features

- Waterproof, conforms to IP66
- One relay, 600 users
- Card type: 125KHz EM card, 125KHz HID card, and 13.56Mhz Mifare Card
- PIN length: 4~6 digits
- Wiegand 26~37 bits input & output
- Can be used as Wiegand reader with LED & Buzzer output
- Pulse mode, Toggle mode
- 2 devices can be interlocked for 2 doors
- 12~28V AC/ DC

Features

User Capacity	600
Operating Voltage	12~28V AC/DC
Current	< 65mA (Idle Current), < 100mA (Active Current)
Radio Technology	125kHz & 13.56Mhz
Read Range	2~6 cm
Wiring Connections	Relay output, exit button, alarm, door contact, Wiegand input, Wiegand output
Relay	One (NO, NC, Common)
Wiegand Interface	Wiegand 26~37bits
Environment	IP66
Operating Humidity	0% ~ 90%RH
Operating Temperature	-40°C ~ 60°C
Physical	Zinc-Alloy Enclosure
Size	150(L)*51(W)*23(H)mm



EFFICIENT SYSTEMS PTE LTD

BLK 52, UBI AVE 3, #03-42 FRONTIER, SINGAPORE 408867

TEL: +65 68582880 FAX: +65 67435906

www.efficient.com.sg